
smart&smoothoperator® / RS100 io

Somfy reinvents the movement of roller shutters. mastered mouvement







SOMFY REINVENTS THE TUBULAR MOTOR

S&SO
PATENTED TECHNOLOGY



CONNECTED

EASY TO INTEGRATE

AND INSTALL

RELIABLE

Somfy innovates with the first intelligent tubular motor reinventing the rolling shutter movement.

smooth*

100%

MASTERED MOVEMENT
ACOUSTIC COMFORT
PROTECTIVE MOVEMENT

Somfy sets a
new benchmark in
terms of visible quality,
acoustic comfort
and reliability.



smart&smoothoperator°

The 1st intelligent tubular motor More added value to rolling shutters



S&SO RS100 motor

100% CONNECTED

An outstanding connected motor

- It meets the integrator's traceability demands.
- Compatible with TaHoma and Connexoon for a connected home and equipment.
- It is ready for the connected home.



SIMPLE TO INTEGRATE

Makes a difference from the integration

- The S&SO RS100 motor is adapted to the assembler's manufacturing process.
- Motor settings can be customized for each shutter.
- Increased productivity: pairing by barcode and roll up in high-speed mode (>32rpm).



EVEN MORE ADDED VALUE WITH THE NEW CONFIGURATION TOOL

EMS2

Benefit from all the advanced features of the S&SO RS100 motor from integration. Fully integrated during your manufacturing process: no risk of a mistake!





100% EASY TO INSTALL

The 1st Plug & Play wireless motor

All S&SO RS100 motors are double-insulated. Fully adaptable: to suit every kind of installation. Setting or resetting limit end-limits is intuitive, without a double power cut, and with automatic detection of the rotation direction.

EVEN MORE ADDED
VALUE WITH THE
INSTALLATION TOOL
SET&GO io
Benefit from all
the advanced features
of S&SO RS100 with the
Set&Go io installation.

• S&SO RS100 io, for renovation projects:



100% secure technology, optimal radio reliability. Real time feedback. Protocol shared with the major connected home brands.

• S&SO RS100 io Hybrid, for new-build:



A motor drive that combines wired controls and io-homecontrol® radio technology to prepare the site for the home automation world.



- Five times more reliable.
- Components and technology tested over 17,500 cycles.



smart&smoothoperator°

Somfy is reinventing the way the rolling shutter moves

A feeling of well-being in the home

MASTERED SMOOTH MOVEMENT

- The S&SO RS100 benefits from Soft start/Soft stop.
- Movement is totally controlled, coming to a gentle stop to protect the rolling shutter.
- Two-speed motor, to adapt the movement of the shutters to suit your preferences.

ACOUSTIC COMFORT

- The S&SO RS100 motorized shutter provides enhanced acoustic comfort in the house.
- In "discreet mode" the rolling shutter is silent.



Make silence the new standard. By choosing the Somfy DESIGNED FOR SILENCE motor drives, you provide unparalleled acoustic comfort.

PROTECTIVE MOVEMENT

- Detection more sensitive of the obstacle.
- Automatic adjustment of sensitivity threshold to the obstacle detection.
- The S&SO RS100 motor is fitted with a frost detector.



S&SO RS100 motor is equipped with SMART PROTECT function

This function provides an extra protection of the rolling shutter.



S&SO RS100, An ACT FOR GREEN motor

Somfy is committed to reducing its environmental impact with eco-designed products.



CONFIGURATION TOOL EM52



MORE THAN A MOTOR, A COMPLETE ECO-SYSTEM

Smart&Smooth Operator combines the best of Somfy's innovation, for greater productivity during integration and installation, more custom-made solutions, a superior maintenance service and greater comfort for the inhabitants.

INSTALLATION TOOL SETAGO IO



MOTORS S&SO RS100 io S&SO RS100 io HYBRID




CHOICE OF CONTROL

io CONTROLS (Smoove RS100 io, Situo io, Nina io) AND CONNECTED SOLUTIONS (TaHoma, Connexoon)

THE NEW STANDARD FOR ALL ROLLING SHUTTERS

For all sizes of shutters, with or without rigid links and end-limits. Compatible with io-homecontrol® technology, 100% Plug & Play.

S&SO RS100 io / S&SO RS100 io HYBRID



-			
Power supply	230 V		
Power supply range	195.5 - 255 V		
Frequency	50 Hz		
Connections	io: 2 / io HYBRID : 4		
Cables	0.75 mm ²		
Protection index	IP44		
Operating temperature	Normal use: -10°C to +40°C Exceptional use (20% of operating life, not simultaneous): -25°C to +70°C		
Certifications	CE OPE CERCIFIE		

PERFORMANCE					
Nominal torque (Nm)	6	10	15	20	
Nominal speed (rpm)	17 rpm	(Adjustable between 12 rpm and 17 rpm)			
Discreet speed (rpm)	8 rpm	(Adjustable between 6 rpm and 10 rpm)			
Rated power (W)	40	55	80	100	
Max. intensity (A)	0,3	0,4	0,65	0,8	
Weight (kg)	1,198	1,323	1,452	1,673	
DIMENSIONS (mm)					
L1 max.	464	478	521	538	
L2 (+ 3mm)	449	463	506	523	
L3 max.	470	484	527	544	
Tube	410	424,2	467	484,5	



io-homecontrol°

100% secure technology, optimal wireless reliability. Real time feedback.

Protocol shared with the major connected home brands.



io HYBRID

Combination of a wired and a wireless installations. Ideal for new build.

Access connected home with a wired motor is now possible.

CONTROL OPERATING MODES

CONNECTED SOLUTIONS



TaHoma®

Web operating interface to control all equipment in the home.



Connexoon® Window

Dedicated interface to control "Window" equipement: Rolling shutters, external Venetian blinds, Velux, alarm, light, sensors and plugs.

CONTROLS



Nina Timer io

Touch-screen control for operating the io-homecontrol® equipment in the house. Programmable clock functions, centralization, feedback.



Nina io

Touch-screen control for operating io-homecontrol® equipment in the house. Centralized functions, feedback.



Situo 1 et 5 io

1-channel or 5-channel remote control.



Smoove RS100 io

1 channel wallmounted control. Discreet function mode.

Somfy SAS

50 avenue du Nouveau Monde BP 152 - 74307 Cluses Cedex France T +33 (0)4 50 96 70 00 F +33 (0)4 50 96 71 89 www.somfy.com

A BRAND OF **SOMFY** GROUP

